



3 Ply Waterproof Sealing Tape

A high grade waterproof sealing tape system for internal and external domestic and commercial applications including those under constant positive pressure consisting of:

- 10m / 50m Tapes
- Internal / External Corners
- Pipe Inlet Collar

DESCRIPTION

A specially coated 120mm wide 3 ply tape with 2 outer layers of non-woven polypropylene coated with thermoplastic elastomere, resistant to ageing.

APPLICATION

To be used in conjunction with ROCATEX Waterproof Tanking Coat - please refer to separate technical data sheet.

Apply first coat of ROCATEX Waterproof Tanking Coat and whilst still wet firmly press in the sealing tape / corners / pipe inlet collars. Once dry (approximately 15 minutes) a second coat should be applied. Tiling can commence once the second coat has fully cured, approximately 1 hour at 20°C.

Suitable for medium to high loads of non-pressurized water indoors (e.g. showers, wetrooms, bathrooms, steam rooms - both domestic and commercial). It can also be used for water under constant positive pressure, both internal and external (e.g. swimming pools, balconies and terraces).

TECHNICAL DATA

Substrate:	2 outer layers of non-woven polypropylene
Coating:	Thermoplastic elastomere, resistant to ageing
Colour:	Dark grey
Total width:	120mm
Total thickness (approx.):	0,70mm
Material weight (approx.):	43g/m
Resistance to temperature, min. / max:	-30°C / +90°C
Length per roll:	10m / 50m
Certified according to:	DIN EN ISO 9001: 2008
Warranty:	5 years warranty for the guaranteed product qualities
Burst pressure, max:	Internal >2,0 bar
Breaking load longitudinal:	104 N / 15mm
Breaking load:	23 N / 15mm
Extension break longitudinal:	70%
Extension break:	335%
Power absorption at 25% Elasticity lateral:	0,3 N/mm
Power absorption at 50% Elasticity lateral:	0,3 N/mm
Resistance to water pressure:	>1,5 bar
UV-Resistance, min:	500 h

ROCATEX

Rocatex Ltd
Units 3+4 Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com