



## Butyl Waterproof Sealing Tape

Self-adhesive waterproof sealing tape for internal domestic applications consisting of:

- 10m / 50m Tapes

### DESCRIPTION

A 100mm wide non-woven butyl rubber coated self-adhesive tape. 2 overlapping easy-peel release liner backing strips allows for easy application to joints. Can also be used as a reinforcing tape for the butt-edges of tile backer boards.

### APPLICATION

To be used in conjunction with ROCATEX Waterproof Tanking Coat but with a different application procedure to the 120/70 and 3 Ply tapes.

Ensure the substrate is clean and free from dust or any other contaminants which will impede adhesion. Peel off backing strips and firmly press the sealing tape to the substrate. Apply the first coat of ROCATEX Waterproof Tanking Coat, once dry (approximately 15 minutes) a second coat should be applied. Tiling can commence once the second coat has fully cured, approximately 1 hour at 20°C.

Suitable for indoor application for medium loads of non-pressurized water (e.g. domestic bathrooms).

### TECHNICAL DATA

Substrate:	Non-woven polypropylene
Coating:	Self-adhesive butyl rubber, highly elastic, resistant to ageing
Colour:	Grey
Total width:	100mm
Total thickness (approx.):	0,85mm
Material weight (approx.):	72g/m
Resistance to temperature, min. / max:	-5°C / +60°C
Length per roll:	10m / 50m
Certified according to:	DIN EN ISO 9001: 2008
Warranty:	5 years warranty for the guaranteed product qualities
Burst pressure, max:	Internal >0,4 bar
Breaking load longitudinal:	32 N / 15mm
Breaking load:	23 N / 15mm
Extension break longitudinal:	54%
Extension break:	81%
Power absorption at 25% Elasticity lateral:	0,9 N/mm
Power absorption at 50% Elasticity lateral:	1,3 N/mm
Resistance to water pressure:	>0,2 bar
Peel test on neutral PVC carrier:	Internal >10 N / 20mm

### ROCATEX

Rocatex Ltd  
Units 3+4 Camwal Park  
Camwal Road  
Harrogate, HG1 4PT

T: +44 (0)1423 882 990  
F: +44 (0)1423 299 040  
E: [info@rocatex.com](mailto:info@rocatex.com)  
[www.rocatex.com](http://www.rocatex.com)