



## C-10 Ultimate Grout Sealer

**A high performance VOC free water-based impregnating grout sealer which provides an invisible, durable, protective barrier against stains, dirt, mould and limescale. The highly water repellent formula does not alter the grout colour.**

- Suitable for Wall & Floor Grout Joints
- Also for Stone / Concrete / Brick / Render
- Excellent Stain & Dirt Protection
- Fights Against Mould & Limescale
- Easy to Apply - Only 1 to 2 Coats Required
- Invisible Finish - Does Not Alter Grout Colour
- Highly Repellent Long Lasting Protection
- Interior / Exterior / Domestic / Commercial

### DESCRIPTION

A high performance VOC free water-based impregnating grout sealer designed using the very latest technology in fluorochemistry. This versatile and easy to apply penetrating and invisible sealer provides a durable, non-film-forming protective barrier on wall and floor grout joints, porous acid sensitive surfaces including polished and unpolished natural stone, paving, concrete and render. ROCATEX C-10 Ultimate Grout Sealer allows the surface to breathe and provides excellent oil, grease and water repellency, stain resistance and ease of cleaning.

### DIRECTIONS

Shake the bottle before use and ensure surface to be treated is completely clean, dry and free from dirt, grime and any excess cement and grout residues. If necessary, first wash the surface with a dilute solution of ROCATEX Tile & Stone Renovator 1:10. Rinse well to remove residues and leave to dry. It is important to remove any factory applied sealer or wax from the surface of porcelain before sealing.

Adjust the nozzle according to the width of spray required. Hold the spray 15-20cm away from the grout joint and apply generously ensuring the solution covers the entire grout joint. Remove any excess sealer from the tile with a lint free cloth and after 15-30 minutes remove any excess sealer from the grout joint. A second application is recommended after 1 hour to ensure complete coverage and again remove any excess sealer after 15-30 minutes.

Treated areas should be dry enough to walk on after about 1 hour but will take 72 hours to become fully resistant. During this time DO NOT cover the surface and wipe up any spills immediately. Consideration should also be given to any moisture trapped in a surface on newly laid floors in terms of covering the surface after sealer application.

To check that the surface has been adequately sealed a simple water bead test can be performed. This is achieved by applying a teaspoon of water onto the sealed surface and leave for 15 minutes, if bead is absorbed then another coat is required. Do not apply in direct sunlight or in temperatures exceeding 25°C. Do not allow any residues to dry on the surface and you must NOT apply if an underfloor heating system is on. Tip: Without prior experience or in cases of doubt, try the product in an inconspicuous area prior to use.

### COVERAGE

Up to 500 linear metres per 500ml depending upon the width of the grout joint and number of coats required.

## ROCATEX

Rocatec Ltd  
3+4 Camwal Park  
Camwal Road  
Harrogate, HG1 4PT

T: +44 (0)1423 882 990  
F: +44 (0)1423 299 040  
E: [info@rocatex.com](mailto:info@rocatex.com)  
[www.rocatex.com](http://www.rocatex.com)

This information is offered without guarantee. Our Company policy is one of continuous research and development, we therefore reserve the right to update this information at any time without prior notice. We guarantee the consistent high quality of our products, however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. If in doubt, conduct a small test or obtain further technical advice.

## MAINTENANCE

Routinely sweep the floor and wash with ROCATEX Tile & Stone Cleaner, clean walls and work surfaces with ROCATEX Tile & Stone Cleaner.

## STORAGE

Store in a cool, dry, frost-free environment between +5°C and +25°C. Shelf life can be up to 2 years in the original unopened containers.